



CAT# 71432
Designer WallPack



Model :		71432
OVERALL LAMP PARAMETERS	Input Voltage	100-277VAC
	Input Current	0.6A Max.
	Input Power	50W
	Power Factor	PF≥ 0.9
	Luminance	5000
	Luminous Efficiency	83 LM/W
	CRI	>80
	Beam Angle	90°
	Main Structure	PC
	Surface	Baking Varnish
LED DRIVER	Output Voltage	40-66 VDC
	Output Current	0.75A
	Driver Efficiency	85%
LED	LED Type	SMD
	LED Quantity	70 PCS
	LED Manufacturer	Philips 3030-2D
	LED Efficacy	140 lm/W
	Color Temperature	WW/NW/CW
LIFESPAN & ENVIRONMENT	Lifespan	50000 Hrs.
	Warranty	5 Years
	IP Rating	IP65
	Operating Temperature	-40F to 131F
	Storage Temperature.Humidity	-40°C—+80°C , 10—90% RH
SAFETY&EMC	Safety Norms	EN60598, EN61347-2-13, EN62031, EN62471, UL1598, UL8750
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	25A 100mΩ
	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
OTHERS	Diamension	Pls refer to attached dimension drawing
	Net Weight(Kg)	2.9
	Gross Weight(Kg)	3.35
	Carton Size	320*280*195
	Q'ty / Carton	1

Dimensions:

