

# DEFY ELASTOMERIC FLASHING SEALANT

## PRODUCT NAME

### DEFY Elastomeric Flashing Sealant

MANUFACTURER SaverSystems  
Richmond, IN 47374  
800-860-6327  
Fax 765-935-4999  
www.defyinfo.com

## DESCRIPTION

DEFY Elastomeric Flashing Sealant is an elastomeric sealant specially formulated for permanent adhesion to asphalt shingles, aluminum flashing, brick, and other chimney and roofing materials.

## USES

DEFY Elastomeric Flashing Sealant is excellent for use in stopping problem leaks around the base of chimneys, stacks, and vents. It is also great for sealing around skylights. Repairing flashings that have been tarred, re-tarred, cracked, or just plain funky has never been so easy.

## BENEFITS

- Stays flexible
- Available in black, brown, and white
- Easy brush-on application

## DIRECTIONS FOR USE

**Preparation:** Clean surfaces to which product will be applied with stiff brush to remove any dust, dirt, or debris. Measure and cut enough reinforcement fabric to completely cover the repair. Work the lowest side of the chimney or vent first.

**Note:** White DEFY Elastomeric Flashing Sealant can be colored using any standard mortar dye. To color, remove all the DEFY Elastomeric Flashing Sealant you will need for the job to another container and add mortar dye one drop at a time, mixing until desired color is reached.

## APPLICATION

Stir product well. Apply approximately 1/8" of coating to the surface to be sealed. Make sure product fills all cracks and holes entirely and extends about one inch beyond the edges. The DEFY Elastomeric Flashing Sealant should extend beyond the edges. Apply a liberal topcoat of DEFY Elastomeric Flashing Sealant making sure to completely cover the surface and extend beyond the problem area about one inch.

**Note:** On hot days DEFY Elastomeric Flashing Sealant will dry quickly. Work in 2-3 ft. sections. Use of duct tape will produce clean edges and enhance the appearance of the repair. Coverage: 1/2 gallon of DEFY Elastomeric Flashing Sealant covers approximately 14 linear feet.

**Clean-Up:** Soap and water while product is still wet.

**Note:** Do not use in cold, damp rainy weather or product may wash away. Allow at least 12 hours of dry, clear weather for proper curing. Apply at temperatures above 45° F.

## CAUTIONS

**Keep away from children.** Respiratory protection is not generally required during normal use and handling. The use of protective gloves and chemical splash goggles is recommended. Wash thoroughly after handling. Close container after each use. Use protective clothing to avoid contact with skin and eyes.

**First Aid: External:** Wash skin with soap and water. **Eye contact:** Immediately flush with clean water for fifteen minutes. Consult a physician. For additional information, consult the Material Safety Data Sheet for this product.

## LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from defects.

SaverSystems liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor for application. SaverSystems shall not have any other liability including direct,

incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

## PACKAGING

DEFY Elastomeric Flashing Sealant is available in one half gallon plastic containers.

## TRANSPORT AND STORAGE

DEFY Elastomeric Flashing Sealant is not considered a hazardous material or substance under U.S. Department of Transportation (DOT) regulations. Store DEFY Elastomeric Flashing Sealant in a cool, dry place inaccessible to children and animals.

Do Not Freeze.