

72706SB1

6' Mini Personal SRL with Steel Snap Hook, Includes Steel Dorsal Connecting Carabiner

Features :

- Features internal locking pawls and ViewPack® external energy absorber for even deceleration
- Long-wearing Dyneema® web lifeline resists abrasion while providing trusted strength.
- Nylon housing provides impact resistance in most worksite conditions
- Plated steel swivel-eye helps to prevent lifeline twisting and provide smooth operation
- Features alloy steel snap hook anchorage connector
- Includes alloy steel dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14-2014



Material Specifications	
Webbing	Dyneema®/Polyester blend; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,000 lb min.
ANSI SRL Class	Class B
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	54"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.14-2014
OSHA	1926.502 and 1910.66
CSA	Z259.2.2-2017

Sizes & Part Numbers		
72706SB1 (ANSI Compliant)	C72706SB1 (CSA Compliant)	