

## Fireplace Patch

### Item 62

- For making repairs in fireboxes
- For repairing outdoor firepits
- Withstands 2200°F
- Cures without heat



### Description:

A dry mix material, which when mixed with water, chemically sets as hard as a brick. Use it to make repairs and fill holes in masonry fireboxes.

### Performance Characteristics:

- Cures without heat
- Sets as hard as a brick
- Withstands 2200°F

### Recommended Uses:

Excellent for use in repairing outdoor firepits. Make repairs and fill holes in masonry fireboxes.

### Surface Prep:

Wear rubber gloves and appropriate eye protection. Protect work area with drop cloth. Clean all loose or foreign matter away from the surface to be cemented. Dampen work area lightly with water.

### Application:

Stir the dry contents of the container thoroughly. Using a plastic bucket or container, add three (3) fluid ounces cool clean water to the dry mix. Mix thoroughly taking care not to lose any water which contains the binder. Pour into the hole or crack and smooth by patting thoroughly to remove air pockets. Do not smooth to a slick finish, this inhibits escaping water. It sets up in 20-30 minutes. Let set at 60°F or above for 24 hours. Do not permit surface

to dry out during this period. Heat slowly when first starting fire.

### Coverage:

600 grams fills holes up to 15 cubic inches.

### Clean up:

Wipe up spills and clean up immediately with warm water.

### Typical Physical Properties:

Service temperature	2200°F
Consistency	Dry
Flashpoint	N/A
Pot Time	20-30 minutes
Dry Time	24 hours, depending upon thickness, humidity and air temperature
Color	Gray
Storage/Handling	Keep cover closed tightly Store in a dry place

### Limitations:

Will not adhere to metal surfaces. Do not add any colorants. Dried Fireplace Patch contains some chemically combined water that is given off as steam at high temperatures; therefore, apply heat gradually when first starting the fire.

### Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18)

months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

**Limitation of Liability:**

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company

product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**CAUTIONS:**

**Contains Portland Cement. Product is alkaline. Avoid contact with eyes and prolonged contact with skin. Wear safety glasses and rubber gloves. In case of contact, flush with plenty of water. For eyes, flush with water for at least 15 minutes. Get immediate medical attention. Avoid breathing dust. Use NIOSH approved dust respirator.**

**KEEP OUT OF REACH OF CHILDREN  
EYE AND SKIN IRRITANT  
HARMFUL IF SWALLOWED**