

Glass Cleaner - For Fireplace Doors & Stoves

Item 82

- Effectively cleans soot, grime and creosote from glass & hearth
- Ultra cling formula
- Spray on, wipe off



Description:

An all-purpose, hard-surface cleaner particularly effective against the sticky by-products of wood combustion such as soot and creosote. Especially effective in dissolving gummy residue build-up on wood stove and fireplace glass doors.

Performance Characteristics:

- Non-abrasive, will not scratch
- Non-toxic and non-corrosive

Recommended Uses:

Use on glass doors of fireplaces and wood stoves. May also be used on fireplace screens, frames and accessories, woodstoves, and hearth.

Application:

Glass doors on fireplaces: Use on cool glass only. Use to clean glass doors, screens and frames or removable glass screens of woodstoves. Spray on and wipe clean with paper towels. Thoroughly remove all traces of cleaner before it dries. If soot and creosote are baked on the glass, repeat the application. If a soft abrasive is needed for a particularly difficult stain, try Rutland's Item 84, Hearth & Grill Conditioning Glass Cleaner.

Woodstoves: Let stove cool. Spray on iron and steel woodstoves, rinse and wipe off with paper towels. Thoroughly remove all traces of cleaner before it dries. Effective for use inside and out.

Fireplace Accessories: Spray on, rinse and wipe off with paper towels. Thoroughly remove all traces of cleaner before it dries.

Hearth: Test clean an inconspicuous spot to ensure compatibility of masonry and cleaner before proceeding with entire job. Dampen area to be cleaned with water. Spray liberally. Scrub with a hard bristle brush to loosen soot from deep pores of masonry. Rinse and dry. Do not allow cleaner to dry before removal.

Clean up:

Clean up with water. If overspray is allowed to dry on glass, use Rutland's item 84 or 565 to remove residue.

Typical Physical Properties:

Solvents	Water, dipropylene glycol methyl ether
Weight/Gallon	8.4
Consistency	Liquid
Flashpoint	N/A
Color	Clear
Storage/Handling	Store right side up. Rotate stock.

Limitations:

Not recommended for painted surfaces. Do not use near food.

Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18)

months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage

arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

CAUTIONS:

Eye irritant. Contains glycol ether and sodium metasilicate. Avoid contact with eyes and skin by wearing safety goggles and rubber gloves. In case of eye contact, flush with plenty of water for at least 15 minutes. For skin contact, flush with water. If swallowed, give plenty of water and contact a physician immediately.

**KEEP OUT OF REACH OF CHILDREN
EYE IRRITANT**